

POINT POD CONNECT - MODEL SPECIFICATIONS

SPECIFICATIONS	POINT POD CONNECT SILVER	POINT POD CONNECT BLACK	POINT POD CONNECT 65W SILVER	POINT POD CONNECT 65W BLACK
				
Model Number	PPCV815	PPCV815B	PPCV815PD	PPCV815PDB
Finishes	Anodised Aluminium	Anodised Black	Anodised Aluminium	Anodised Black
Electrical Data	125ac 60Hz 15a / 1875W	125ac 60Hz 15a / 1875W	125ac 60Hz 15a / 1875W	125ac 60Hz 15a / 1875W
Hole Size Ø	4.0 in or 101.6mm	4.0 in or 101.6mm	4.0 in or 101.6mm	4.0 in or 101.6mm
Dimensions				
Inner Disc Ø	3.66 in or 93 mm	3.66 in or 93 mm	3.66 in or 93 mm	3.66 in or 93 mm
Height (Closed)	16.15 in or 410 mm	16.15 in or 410 mm	16.15 in or 410 mm	16.15 in or 410 mm
Height (open)	22.8 in or 580 mm	22.8 in or 580 mm	22.8 in or 580 mm	22.8 in or 580 mm
Mounting Flange Diameter	6.3 in or 165 mm	6.3 in or 165 mm	6.3 in or 165 mm	6.3 in or 165 mm
Cabinet Depth Required	17.72 in or 450 mm	17.72 in or 450 mm	17.72 in or 450 mm	17.72 in or 450 mm
Socket Configuration	2 x North American outlets 1 x USB-A (3.0 A) 2 x USB-C (3.0A)	2 x North American outlets 1 x USB-A (3.0 A) 2 x USB-C (3.0A)	2 x North American outlets 2 x USB-C PD (65W MAX)	2 x North American outlets 2 x USB-C PD (65W MAX)
Weight	6.6 lb or 3 kg	6.6 lb or 3 kg	6.6 lb or 3 kg	6.6 lb or 3 kg
Cable Length	6 ft or 1.8 m	6 ft or 1.8 m	6 ft or 1.8 m	6 ft or 1.8 m
Warranty	2 Years	2 Years	2 Years	2 Years
Certifications	ETL Listed, UL962A CSA C22.2 IP44	ETL Listed, UL962A CSA C22.2 IP44	ETL Listed, UL962A CSA C22.2 IP44	ETL Listed, UL962A CSA C22.2 IP44

Compliance with NEC 406.5(E) can be achieved by connecting it to a GFCI-protected circuit during installation. This setup ensures necessary protection against ground faults.